

Walcoom Corporation



There are 26 kinds of Walcoom chain link fence accessories with different sizes while used in the installation of chain link fence. In order meet the actual use of chain link fence, Walcoom gives you accurate size of each accessory in this document, also display the specific usage of each accessory.

1. Brace band application image as bellow:



Round shape brace band

Specification of brace band

- Material: pressed steel.
- Surface treatment: hot-dip galvanized or PVC-coated.
- Color: match the color coating of the fabric.
- Minimum thickness: 12 gauge.
- Minimum width: 3/4".
- Size: 1-3/8", 1-5/8", 2", 2-1/2", 3", 4", 6".

2. Tension band application image as bellow:



Galvanized tension band

Specification of Tension band

- Material: pressed steel.
- Surface treatment: hot-dip galvanized or PVC-coated.
- Color: match the color coating of the fabric.
- Minimum thickness: 14 gauge.
- Minimum width: 3/4".
- **Size:** 1-3/8", 1-5/8", 2", 2-1/2", 3",3-1/2", 4", 6".

3. Two types of bullet post cap as bellow:








One-way bullet post cap

Specification of bullet post cap

- Material: steel, aluminum.
- Surface treatment: galvanized or vinyl-coated.
- Color: silver, black, green, brown or custom colors.
- Weight: 4.3 bounce.
- Post size: 2-1/2" (2-3/8". Actual).
- Style: 0-way, 1-way and 2-way.

4. Hog rings application image as bellow:



Chain link fence hog rings


Specification of hog ring

- Material: steel.
- Surface treatment: galvanized or vinylcoated.
- **Color:** silver, black, green, brown or as required.
- Wire gauge: 9 gauge, 11 gauge, 14 gauge.
- **Size:** 3/4", 1/2", 3/8".
- Auxiliary tool: pliers.

5. Safety top cap application image as bellow:









Safety top cap

Corrugated tubing fence top

Safety topper cap on chain link fence

Corrugated tubing fence top cap


Specification of safety top cap

- Material: UV stabilized HDPE (high density polyethylene).
- Safety top cap
 - ◆ Color: yellow, red, green, blue, black, orange, etc.
 - ◆ Thickness: 1/16".
 - Height: 1/2".
 - Width: 2 3/4".
 - Length: 8 ft.
 - Package: 10 pcs/box.
 - Accessories: hog-rings or zip-ties.

Corrugated tubing fence top cap

- ◆ Color: yellow & black.
- Diameter: 4 1-2".
- ◆ Thickness: 1/16".
- Roll length: 100 ft & 250 ft.
- Warranty: 3 years.
- Accessories: cable ties.

6. Tension bar application image as bellow:



Specification of tension bar

- Material: steel.
- Surface treatment: hot-dip galvanized or vinyl-coated.
- Width: 5/8", 3/4", 3/8".
- Thickness: 3/16", 1/4".
- **Height:** 36", 42", 48", 60", 72", 84", 96", 108", 120", 144".

7. Chain link fence slat application image as bellow:





Ridged chain link fence slat

Winged chain link fence slat

Specification of chain link fence slat

- Slat material: plastic tubes slat, aluminum slat, high-density polyethylene slat, plastic coated slat.
- **Color:** light blue, white, green, brown, blank, etc.

Specification table						
Ridged slat	Slat width	Mesh size	Wire gauge	Slats per bag	Approx coverage per box	
	1 3/32"	2"	8", 9", 11"	82	10 linear feet	
	1 1/4"	2 1/4", 2 3/"8	11 1/2", 12 1/2"	78	10 linear feet	
	7/8"	1 3/4"	8",9", 11"	97	10 linear feet	
Winged slat	1 1/4"	2"	9"	82	10 linear feet	

8. Tension wire application image as bellow:





Spring tension wire

www.walcoom.com E-mail: sales@walcoom.com

Specification of tension wire

• Material: steel wire.

• Surface treatment: galvanized, PVC coating, metallic coating.

• Color: green, silver, black, brown.

• Wire gauge: 7 gauge, 9 gauge, 11 gauge.


• Length: 1000 feet/coil.

Table 1 Breaking Strength of Metallic-Coated Core Wire				
Specified diameter of core wire inch. (mm)	Minimum breaking strength ibf (N)			
0.177 (4.50)	1950 (8670)			
0.148 (3.76)	1290 (5740)			

Table 2 Weight of Metallic Coatings					
Specified diameter of core wire, inch. (mm) Minimum weight of zinc coating, oz/ft (g/m²)		Minimum weight of aluminum coating oz/ft² (g/m²)	Minimum weight of zinc-5 % aluminum-mischmetal coating oz/ft² (g/m²)		
0.177 (4.50)	0.40 (122)	0.20 (61)	0.40 (122)		
0.148 (3.76)	0.30 (92)	0.20 (61)	0.30 (92)		

Table 3 Thickness of Polymer Coating				
	inch. (mm)	inch. (mm)		
Minimum thickness at any point	0.015 (0.38)	0.006 (0.15)		
Maximum thickness at any point	0.025 (0.64)	0.012 (0.30)		

9. Fence tie application image as bellow:



Metal fence ties

Specification of fence ties

• Material: aluminum.

• Surface treatment: vinyl-coating, galvanized.

• Color: silver, black.

• Wire gauge: 9.

• Length: 6-1/2", 8-1/4".

Package: 30 pcs/bag.

10. Post cap type image as bellow:



Dome-shape post cap

Specification of post cap

• Material: aluminum or steel.

Surface treatment: galvanized or vinyl-coated.

Style: dome and acorn post cap.

• Post size: 1-3/8", 1-5/8", 2", 2-1/2", 3", 4", 6-5/8".

11. Line post cap application image as bellow:



Line post cap

Specification of line post cap

• Material: pressed steel or aluminum.

• **Size:** 1-5/8" × 1-3/8", 1-5/8" × 1-5/8", 2" × 1-3/8", 2" × 1-5/8", 2-1/2" × 1-5/8", 3" × 1-5/8", 3-1/2" × 1-5/8", 4" × 1-5/8".

12. Rail end application image as bellow:



Rail end with hook

Specification of rail end


• Material: aluminum or steel.

• Surface treatment: zinc-coating or vinyl-coating.

• **Diameter:** 1-3/8", 1-5/8" and 2".

13. Barbed wire arm application image as bellow:





Specification of barbed wire arm

• Material: pressed steel.

• Surface treatment: hot-dip galvanized.

• Size: 1-5/8" × 1-5/8", 2" × 1-5/8", 2-1/2" × 1-5/8".

• Style: single slanted arm for three barbed wire strands; V-shaped arm for six barbed wire strands.

14. Carriage bolt application image as bellow:



Carriage bolt

Specification of carriage bolt and nut

• Material: steel.

• Surface treatment: hot-dip galvanization.

• Diameter: 5/16 & 3/8 inch.

• Length: 1-1/4, 1-1/2, 2, 2-1/4, 2-1/2, 3 & 3-1/2 inch.

Nut is included.

15. Top rail sleeve type image as bellow:



Metal top rail sleeve



Black vinyl-coated rail sleeve

Specification of top rail sleeve

• Material: steel.

 Surface treatment: galvanized or vinylcoated (match with the fence fabric).

• Outside diameter: 1-3/8, 1-5/8 and 2 in.

• Wall thickness: 17 gauge.

• Length: 6" & 7".

16. Top rail application image as bellow:



Metal top rail

Specification of top rail

Material: steel.


• **Surface treatment:** galvanized or PVC-coated (match with the fence fabric).

• Out diameter: 1-3/8" & 1-5/8".

• Wall thickness: 9 to 17 gauge.

• Length: 21 and 24 ft.

17. J-bolt hinge application image as bellow:



Specification of J-bolt hinge

• Material: pressed steel.

• Surface treatment: zinc-coating or PVC-coated.

• Color: silver, black, green or custom colors.

• Pin diameter: 5/8".

• Length: 4-1/2", 10" and 12".

18. Lag screw hinge application image as bellow:



Lag screw hinge

Specification of lag screw hinge

Surface treatment: galvanization or vinyl-coating.

• Pin diameter: 5/8".

• Length: 4-1/2" and 6".

Usage: farm gates and wood gates.

19. Gate frame hinge application image as bellow:



Gate frame hinge and nuts

Specification of gate frame hinge

• Material: pressed steel.

Surface treatment: galvanized or vinyl-coated.

• Color: silver, black, green or as required.


• Male strap hinge (O.D): 1-3/8", 1-5/8", 2", 2-1/2", 3".


• Female strap hinge (O.D): 1-3/8", 1-5/8", 2".

The types and installation notes as bellow



Female and male gate frame hinges





Installation picture of gate frame hinges

20. Fork latch application image as bellow:



Gate fork latch

Specification of gate fork latch

- Material: pressed steel.
- Surface treatment: galvanized or vinyl-coated.
- Color: silver, black, green or as required
- Clamp size: 1-3/8", 1-5/8" and 2".
- Fork size: 1-3/8", 2", 2-1/2" and 3".
- Usage: single swing gate or double-leaf door.

21. Chain link mount hinge application image as bellow:



Chain link mount hinge

Specification of chain link mount hinge

Material: pressed steel.

• Surface treatment: hot-dip galvanization

• Plate: 1-1/2" × 4" and 2-3/4 " × 5".

Pin diameter: 5/8".

22. Gate clip application image as bellow:



Gate clip

Specification of gate clip

Material: steel.


 Surface treatment: hot-dip galvanization or vinyl-coating.

• Color: silver, black, green and brown.

• Post size: 1-3/8".

• Thickness: 14 gauge.

23. Gate scroll application image as bellow:



Gate scroll

Specification of gate scroll


• Material: steel.

• Surface treatment: galvanized, vinyl-coating.

• Length: 18", 24", 36", 48".

Hardware: self-tapping screw are supplied.

24. Gate corner application image as bellow:



Gate corner

Specification of gate corner

• Material: steel, aluminum.

• Surface treatment: vinyl coating, galvanized.

• Color: black, silver.

• Gauge: 12 gauge, 14 gauge.

• Matched pipe size: 1-3/8", 2".

• Accessories: self-screw.

25. Razor wire application image as bellow:



Chain link fence with razor wire



Razor wire

Specification of razor wire

Material: galvanized steel or stainless steel AISI 304.

• Surface treatment: galvanized, PVC coating.

• Coil diameter: 450 mm.

• Lineal meters: 7-10 m.

• Thickness: 0.5 mm.

• Wire diameter: 2.5 mm.

• Razor length: 65 mm.

• Razor width: 15 mm.

• Tensile strength: 140 KSI (965 MPa).

• Space between razors: 100 mm.

Package

■ Waterproof paper.

■ Woven bag.

■ Carton.

■ Pallet.

Table 1: Common Specifications of Razor Wire							
Code	Outer Diameter (in.)	Coil Quantity	Covering Length (ft)	Barb Clusters Per Loop	Coil loop Spacing ± 2.0 (in.)	Razor Wire Type	Attachment Points
RW-01	18	31	20	13	16	single coil	3
RW-02	18	51	25	13	12	single coil	3
RW-03	24	31	20	19 ± 1	16	single coil	3
RW-04	24	51	25	19 ± 1	12	single coil	3
RW-05	30	31	20	24 ± 1	16	single coil	3
RW-06	30	51	25	24 ± 1	12	single coil	3,5
RW-07	30	81	40	24 ± 1	12	single coil	5
RW-08	30	101	50	24 ± 1	12	single coil	5
RW-09	40	51	25	31 ± 1	12	single coil	5,7
RW-10	40	81	40	31 ± 1	12	single coil	5,7
RW-11	60	51	25	45 ± 1	12	single coil	9
RW-12	60	81	40	45 ± 1	12	single coil	9
RW-13	24, 30	31	20	43 ± 2	16	double coil	3
RW-14	22	31	20	43 ± 2	16	double coil	3

26. Barbed wire application image as bellow:



Gate corner

Specification of barbed wire

- **Material:** carbon steel wire, aluminum alloy wire, stainless steel wire.
- Surface treatment: galvanized or vinyl coating, PVC coating.
- Color: silver, green, blue, red, black.
- Number of spikes: 4.
- Spike spacing: 70 mm 120 mm.
- Horizontal line wire diameter: 2.8 mm.
- Barb wire diameter: 2.0 mm.
- Length: 1000 ft./roll.
- Wire gauge: 12 gauge, 13 gauge, 14 gauge, 5 gauge.
- Shape of barbed wire: round, flat, half-round.
- Coating thickness: 0.067 0.099 mm.



Add: No. 3481, Yongxing Road, Hengshui City, Hebei Province, China.

Tel: +86-15030811699 Skype: wiremesh@live.com E-mail: sales@walcoom.com Web: http://www.walcoom.com

